



air pollution control district
SANTA BARBARA COUNTY

DRAFT

Permit to Operate 16081

Page 1 of 9

PROPERTY OWNER:

John A. and Dianne M. Wilde

RESPONSIBLE PARTY:

Kerr-McGee Oil & Gas Onshore, LP

EQUIPMENT OWNER:

Kerr-McGee Oil & Gas Onshore, LP

EQUIPMENT OPERATOR:

Kerr-McGee Oil & Gas Onshore, LP, Trihydro Corporation

EQUIPMENT LOCATION:

756 Blue Ridge Drive in Santa Maria, CA

STATIONARY SOURCE/FACILITY:

Blue Ridge Dr, 756 (CSC)

SSID: 11587

FID: 11837

PROJECT/PROCESS DESCRIPTION:

This project involves the excavating, loading, and hauling of up to approximately 300 cubic yards of soil, including 75 cubic yards of hydrocarbon impacted soil. The contaminated soil is known to be in the property located at 756 Blue Ridge Drive in Santa Maria. Stockpiles will be covered with continuous heavy-duty plastic sheeting or treated with the soil binder "Soil-Sement" to reduce fugitive particulates and Reactive Organic Compound (ROC) emissions. The excavated soil will be removed from the site by covered trucks.

DRAFT

Permit to Operate 16081

Page 2 of 9

CONDITIONS:

1. **Operation Limitations.** The permittee shall comply with the following operational limits:
 - a. No chemical defined by District Rule 102 as a Reactive Organic Compound shall be used during the excavation.
 - b. No chemical designated a Toxic Air Contaminant¹ or Candidate Toxic Air Contaminant shall be used during the excavation.
 - c. In the event the project produces nuisance complaints from the general public, the project shall cease immediately and mitigation measures shall be taken to eliminate the nuisance potential. For the purpose of this permit, in addition to the District Rule 303 definition of nuisance, a nuisance shall be considered any one complaint to the District from a resident or business within 1,000 feet of the project or property boundary.
 - d. Contaminated soil shall be transported expeditiously to an approved off-site disposal facility. Stockpiling of contaminated soil in excess of 24 hours after removal from the excavation work area is prohibited without written approval from the District.
 - e. There shall be no visible dust emissions at the excavation site due to the project activities. If visible dust emissions from project activities are detected, removal and loading activities shall cease and dust mitigation measures shall be implemented immediately.

2. **Vapor and Dust Suppression.** The permittee shall comply with the following vapor and dust suppression requirements. The contractor shall designate a person or persons to monitor the dust control program and to order increased dust suppression, as necessary, to prevent transport of dust offsite. The name and telephone number of such persons shall be provided to the District prior to project start-up.
 - a. Contaminated or potentially contaminated soil shall be stockpiled and covered with plastic sheeting or treated with the soil binder "Soil-Sement" at the end of each work day and at all times material is not being added to, or taken from, the stockpiles.²

¹ Substances identified as Toxic Air Contaminants by the Air Resources Board, pursuant to the provisions of AB 1807 and AB 2728.

² This includes all stockpiles that were created from excavated materials. Clean, imported-fill soil is not required to be covered.

DRAFT

Permit to Operate 16081

Page 3 of 9

- b. Open pits and exposed sidewalls shall be covered with plastic sheeting or treated with the soil binder "Soil-Sement" at the end of each work day and when not being worked for 4 hours or more. Exposed sidewalls shall be covered with clean fill dirt or continuous heavy-duty plastic sheeting when excavation activities are not being conducted. Alternatives to the use of plastic sheeting or soil binder "Soil-Sement" may be used upon request and written approval from the District.
- c. All excavated material loaded on transport trucks shall be covered with plastic sheeting or tarps prior to exiting the load-out area and during transit. No openings or holes in the covers shall be permitted.
- d. All plastic sheeting used to fulfill the requirements of this permit shall be either 20 mil heavy duty plastic sheeting or DURA SKRIM 10HUV 10 mil polyester-reinforced polyethylene sheeting. If the District determines at any time that DURA SKRIM 10HUV sheeting is not effective at controlling dust or ROC emissions, the permittee shall apply 20 mil plastic sheeting.
- e. If Soil-Sement binder is used, it shall be applied at a rate of at least 0.28 gallons of concentrate per square yard of treated surfaces. The Soil-Sement binder shall be applied at a ratio of one (1) gallon of Soil-Sement to four (4) gallons of water. If the District determines at any time that the Soil-Sement binder is not effective at controlling dust or ROC emissions, the permittee shall apply heavy-duty plastic sheeting.
- f. If there has been no measurable precipitation during the past three calendar days, water sprays or other adequate measures shall be applied each day that work activities occur to all disturbed areas with the potential to emit fugitive dust. The water sprays or other adequate measures shall be applied at least once during work activities and once at the end of the work day.
- g. Loose dirt and dust shall be removed from all vehicular wheels using brushes, rumble strips, or water prior to leaving the excavation area. If the permittee or the District inspector determines rumble strips are not effective, brushing or water washing shall be the primary method for cleaning wheels. If the permittee or the District inspector determines brushing is not effective, water washing shall be the primary method for cleaning wheels.
- h. Upon completion of soil disturbing activities in each area, soil shall be stabilized to prevent wind erosion.

DRAFT

Permit to Operate 16081

Page 4 of 9

3. **Monitoring.** Upon initiating operations, the permittee shall implement a monitoring program for dust concentrations, ROC concentrations, and odors.

- a. The background dust and ROC concentration shall be measured once every 30 minutes during operations concurrent with the project site boundary air monitoring. The wind direction and wind speed shall be recorded during each background reading. The background concentration shall be measured at 200 feet upwind of the active excavation site.

Alternatively, the background dust and ROC concentration may be established each day prior to daily work commencing by sampling and recording the concentration at 200 feet upwind of the excavation site. Any other method to establish background concentrations must be approved in writing by the District prior to using the method.

- b. Air monitoring for dust concentrations shall be conducted using an active-sampling real-time monitor around the project site boundary at least once every 30 minutes at an interval of not less than 100 feet between monitoring locations. If any dust concentration is greater than $50 \mu\text{g}/\text{m}^3$ above background for 30 seconds at the project site boundary, activities shall cease and water spray or other dust prevention measures shall be immediately used to control emissions. The applicant shall notify the District via phone (805-979-8050) and e-mail (enfr@sbcapcd.org, Attn: *CSC Project Manager*) within 4 hours of discovery of an exceedance at the excavation site. Operations may resume upon demonstration that dust concentrations are below $50 \mu\text{g}/\text{m}^3$ above background.
- c. Air monitoring for ROC concentrations shall be conducted using a Photo Ionization Detector (PID) around the project site boundary at least once every 30 minutes at an interval of not less than 100 feet between monitoring locations. If any ROC concentration is greater than 2 ppmv above background for 30 seconds at the project site boundary, activities shall cease and water spray or other vapor suppression measures shall be immediately used to control emissions. The permittee shall notify the District via phone (805-961-8800) and e-mail (enfr@sbcapcd.org, Attn: *CSC Project Manager*) within 4 hours of discovery of an exceedance at the excavation site. Operations may resume upon demonstration that ROC concentrations are below 2 ppmv above background.
- d. Odor monitoring shall be conducted in the excavation site at least once every 30 minutes during excavation activities. If odors³ are detected at the excavation site, activities shall cease and water spray or other vapor suppression measures shall be immediately used to control emissions. The permittee shall notify the District via phone (805-979-8050) and e-mail (enfr@sbcapcd.org, Attn: *CSC Project Manager*) within 30 minutes of detection of odors at the excavation site. Operations may resume upon demonstration that odors are not detectable at or beyond the excavation site boundary.

³ For the purpose of this permit, odors do not include engine exhaust.

DRAFT

Permit to Operate 16081

Page 5 of 9

- e. Dust concentration and ROC concentration shall be taken at the project site boundary, which is defined in the *Air Quality Monitoring Plan*. Odor monitoring readings shall be taken at the excavation site. The excavation site includes any stockpiles, any areas of disturbed soil, and any active work areas. Air monitoring readings shall be taken at 1.5 meters from the ground (average breathing height).
- f. If the permittee receives written approval from the District to store stockpiles onsite for more than 24 hours, the permittee shall monitor for ROC any stockpile left onsite for more than 24 hours at the beginning and end of every work day and at the beginning of each removal, loading, or grading activity. At least 4 readings shall be taken for each stockpile: one upwind, one downwind, one 90 degrees from the upwind position, and one 90 degrees from the downwind position. For any stockpile with sides greater than 20 feet long, one reading shall be taken every 20 feet around the perimeter of the pile.

The stockpiles shall be monitored by placing the probe inlet at a distance of no more than three inches from the surface of the contaminated soil and, while slowly moving the probe across the soil surface, observing the instrument readout. If an increased meter reading is observed, continue to sample the contaminated soil until the maximum meter reading is obtained. Leave the probe inlet at this maximum reading location for approximately double the instrument response time. Record all ROC concentration readings in a format approved by the District.

- g. ROC concentrations shall be measured by a Photo Ionization Detector (PID) calibrated to Isobutylene, complying with 40 CFR Part 60 Appendix A, EPA Reference Method 21 Section 3 or any equivalent method with prior approval in writing by the District.
- h. Soil sampling shall be done in accordance with the *Site Restoration Plan*. Test results shall be made available upon District request within 21 days of sampling. All test results shall be included in the compliance report.

Upon showing reasonable need, the District may require an increased (or decreased) monitoring frequency. Backup documentation such as instrument calibration, equipment maintenance, chain of custody records and sampling logs shall be available for District review. If documentation is not onsite, the permittee shall produce the required documentation within 7 calendar days of request by the District. The instruments shall be maintained according to manufacturer's specifications.

- 4. **Recordkeeping.** The permittee shall record and maintain the following information. This data shall be maintained for a minimum of three (3) years from the date of each entry and made available to the District upon request:
 - a. Sampling lab analysis results required by Condition 3.h.

DRAFT

Permit to Operate 16081

Page 6 of 9

- b. ROC and dust concentration sampling results and odor monitoring results. A District-approved log shall be maintained (tabular format) that contains the following information on an ongoing basis: site location; permit number; sampling date; ROC concentration results at action boundary (in units of ppmv); dust concentration results at action boundary (units of $\mu\text{g}/\text{m}^3$); odor monitoring results (whether or not odors were detected).
 - c. Actions taken to remedy non-compliance based on sampling results and odor monitoring. These actions shall be documented in a District-approved *CSC Non-Compliance Reporting Form*.
 - d. Records of the daily amount of Soil-Sement binder applied, the Soil-Sement to water ratio, and the daily treated area.
 - e. Dates and number of hours per day of excavation activities.
 - f. Start and end times each day excavation activities occur and reasons for shutting down work (e.g., end of work day, visible dust offsite, ROC or dust concentration action levels exceeded, or detectable odors at or beyond the excavation site).
 - g. Amount of soil excavated per day.
 - h. Description of type and engine size of onsite mobile excavation equipment used.
 - i. Records of treatment/disposal shall be maintained for all contaminated soil removed from this site. Such records shall include identification and location of the generator, the transporter and the receiving facility. In addition, such records shall be signed and dated by each of the above parties indicating the receipt or relinquishment of the contaminated soil at the time custody is transferred.
5. **Reporting.** Within 60 days of the completion of the project, a written report documenting compliance with the terms and conditions of this permit shall be provided by the permittee to the District (Attn: *CSC Project Manager*). The report shall contain information necessary to verify compliance with the emission limits and other requirements of this permit. The report shall be in a format approved by the District. Compliance with all limitations and restrictions shall be documented in the submittals. All logs and other basic source data not included in the report shall be made available to the District upon request. The report shall include all records required by Condition 4.a. – j. above.
6. **Permit Expiration.** This permit is valid for one year from the date of issuance. The District may extend the life of this permit for good cause. To obtain an extension, the permittee shall make the request in writing at least 15 days prior to the expiration of this permit.

DRAFT

Permit to Operate 16081

Page 7 of 9

7. **Discovery of Additional Contamination.** If additional contaminated soil is found that was not detailed in the *Soil Management Plan* and a revised plan is required by the lead agency, the additional contaminated soil shall not be excavated under this permit. A new permit application shall be submitted for the work required by the revised plan.
 - a. **Scope of Project.** The conditions of this permit are valid for the entire length of the project, including excavation, sampling, stockpiling, transportation offsite and backfilling with clean, imported-fill soil. This condition shall not be construed as allowing work beyond one year from issuance or allowing operations to continue beyond what was described in the permit application, *Site Restoration Plan*, *Air Quality Monitoring Plan*, *EHS Approval Letters*.

8. **Initial Operations and District Inspection.** The permittee shall:
 - a. Notify the District in writing (enfr@sbcapcd.org, Attn: *Compliance Manager*) of the initial operation date. This notification shall be provided 7 days prior to initial operations.
 - b. Arrange for an inspection by contacting the District's Compliance Supervisor no later than 24 hours after initial operations commence. The Compliance Division may waive this inspection requirement if an initial inspection is deemed unnecessary to verify that the modifications authorized by this permit are in compliance with District rules and permit conditions.
 - c. As specified in Condition 2, prior to project start-up, provide the name and telephone number to the District for the person or persons designated by the contractor to monitor the dust control program and to order increased dust suppression, as necessary, to prevent transport of dust offsite.

9. **Project Completion.** The permittee shall notify the District in writing (enfr@sbcapcd.org, Attn: *CSC Project Manager*) within one week of completion of the project.

10. **Documents Incorporated by Reference.** The documents listed below, including any District-approved updates thereof, are incorporated herein by reference and shall have the full force and effect of a permit condition for this permit. If any conflict arises between the requirements and limits of this permit and the documents, the requirements or limits that are more protective of air quality shall apply. These documents shall be implemented for the life of the Project and shall be made available to District inspection staff upon request.
 - a. *Site Restoration Plan* (Dated February 2, 2023)
 - b. *Air Quality Monitoring Plan* (Dated March 18, 2023).
 - c. *EHS Approval Letters* (Dates include: May 19, 2023; March 22, 2023)

DRAFT

Permit to Operate 16081

Page 8 of 9

12. **Consistency with Analysis.** Operation under this permit shall be conducted consistent with all data, specifications and assumptions included with the application and supplements thereof (as documented in the District's project file) and the District's analyses under which this permit is issued as documented in the Permit Analyses prepared for and issued with the permit.
13. **Compliance.** Nothing contained within this permit shall be construed as allowing the violation of any local, state or federal rules, regulations, air quality standards or increments.
14. **Severability.** In the event that any condition herein is determined to be invalid, all other conditions shall remain in force.
15. **Conflict Between Permits.** The requirements or limits that are more protective of air quality shall apply if any conflict arises between the requirements and limits of this permit and any other permitting actions associated with the equipment permitted herein.
16. **Access to Records and Facilities.** As to any condition that requires for its effective enforcement the inspection of records or facilities by the District or its agents, the permittee shall make such records available or provide access to such facilities upon notice from the District. Access shall mean access consistent with California Health and Safety Code Section 41510 and Clean Air Act Section 114A.
17. **Reimbursement of Costs.** All reasonable expenses, as defined in District Rule 210, incurred by the District, District contractors, and legal counsel for the activities listed below that follow the issuance of this permit, including but not limited to permit condition implementation, compliance verification and emergency response, directly and necessarily related to enforcement of the permit shall be reimbursed by the permittee as required by Rule 210. Reimbursable activities include work involving: permitting, compliance, CEMS, modeling/AQIA, ambient air monitoring and air toxics.
18. **Nuisance.** Except as otherwise provided in Section 41705 of the California H&SC, no person shall discharge from any source whatsoever such quantities of air contaminants or other material which cause injury, detriment, nuisance, or annoyance to any considerable number of persons or to the public, or which endanger the comfort, repose, health, or safety of any such persons or the public, or which cause, or have a natural tendency to cause, injury or damage to business or property.
19. **Grounds for Revocation.** Failure to abide by and faithfully comply with this permit or any Rule, Order, or Regulation may constitute grounds for revocation pursuant to California Health & Safety Code Section 42307 *et seq.*

DRAFT

Permit to Operate 16081

Page 9 of 9

20. **Transfer of Owner/Operator.** This permit is only valid for the owner and operator listed on this permit unless a *Transfer of Owner/Operator* application has been applied for and received by the District. Any transfer of ownership or change in operator shall be done in a manner as specified in District Rule 203. District Form –01T and the appropriate filing fee shall be submitted to the District within 30 days of the transfer

AIR POLLUTION CONTROL OFFICER

DATE

Attachments:

- Permit Evaluation for Permit to Operate 16081

Notes:

- This permit expires one year from issuance.
- Stationary sources are subject to an annual emission fee (see Fee Schedule B-3 of Rule 210).



air pollution control district
SANTA BARBARA COUNTY

DRAFT

PERMIT EVALUATION FOR
PERMIT TO OPERATE 16081

Page 1 of 3

1.0 BACKGROUND

- 1.1 General: This project involves the excavating, loading, and hauling of approximately 300 cubic yards of soil, including 75 cubic yards of soil contaminated with hydrocarbons. The project site is within 1,000 feet of the property boundary of one school, the Valley Christian Academy, located at 2970 Santa Maria Way in Santa Maria. Thus, a school notice was required for the project. An application for a Permit to Operate was received on April 20, 2023 and deemed complete on June 13, 2023.

Excavated material will be loaded on trucks for transportation offsite. Fugitive dust and ROC emissions will be monitored and mitigated through the use of water sprays, vapor suppressants, covering, and direct offsite removal of excavated soils. Stockpiles will be covered with continuous heavy-duty plastic sheeting or treated with the soil binder “Soil-Sement” to reduce odors, fugitive particulates and Reactive Organic Compound (ROC) emissions. Contaminated soil will be removed from the site and sent to the Santa Maria Regional Landfill in Santa Maria, CA.

- 1.2 Permit History: The project has no permit history.
- 1.3 Compliance History: The project has no compliance history.

2.0 ENGINEERING ANALYSIS

- 2.1 Equipment/Processes: The contaminated soil will be excavated and removed from the site.
- 2.2 Emission Controls: Emission controls include soil stabilization using water, vapor suppressants and covering with continuous heavy-duty plastic sheeting.
- 2.3 Emission Factors: Emission factors were not used.
- 2.4 Reasonable Worst Case Emission Scenario: Emissions were not calculated for this project.
- 2.5 Emission Calculations: Emissions were not calculated for this project as there are no reliable methods for estimating emissions from small soil removal and loading projects such as this.
- 2.6 Special Calculations: There are no special calculations.
- 2.7 BACT Analyses: Best Available Control Technology was not required for this project.

DRAFT

**PERMIT EVALUATION FOR
PERMIT TO OPERATE 16081**

Page 2 of 3

- 2.8 Enforceable Operational Limits: The permit has enforceable operating conditions that ensure that visible dust emissions and odors (organic compounds) do not leave the site.
- 2.9 Monitoring Requirements: Monitoring of the operational limits is required to ensure that they are enforceable. Dust and ROC monitoring at the property boundary are required. Additional monitoring includes PID readings of stockpiled soil and lab analysis of the soil as specified in the *Site Restoration Plan, Air Quality Monitoring Plan, and EHS Approval Letters*.
- 2.10 Recordkeeping and Reporting Requirements: The permit requires that the data which is monitored be recorded and reported to the District.

3.0 REEVALUATION REVIEW (not applicable)

4.0 REGULATORY REVIEW

4.1 Partial List of Applicable Rules:

Rule 201.	Permits Required
Rule 202.	Exemptions to Rule 201
Rule 205.	Standards for Granting Permits
Rule 301.	Circumvention
Rule 302.	Visible Emissions
Rule 303.	Nuisance
Rule 801.	New Source Review - Definitions and General Requirements
Rule 802.	New Source Review
Rule 809.	Federal Minor Source New Source Review
Rule 810.	Federal Prevention of Significant Deterioration

4.2 Rules Requiring Review: None.

5.0 AQIA

The project is not subject to the Air Quality Impact Analysis requirements of Regulation VIII.

6.0 OFFSETS/ERCs

6.1 Offsets: The emission offset thresholds of Regulation VIII are not exceeded.

6.2 ERCs: This source does not generate emission reduction credits.

7.0 AIR TOXICS

An air toxics health risk assessment was not performed for this permitting action.

DRAFT

**PERMIT EVALUATION FOR
PERMIT TO OPERATE 16081**

Page 3 of 3

8.0 CEQA / LEAD AGENCY

The District is the lead agency under CEQA for the project. This project is exempt from CEQA pursuant to the *Environmental Review Guidelines for the Santa Barbara County APCD* (revised April 30, 2015). Appendix A (*APCD List of Exempt Projects*) provides an exemption (2.j.) for the removal and trucking of contaminated soil. The District finds that none of the exceptions listed in CEQA Guidelines Section 15000.2 are applicable to the project. No further action is required.

9.0 SCHOOL NOTIFICATION

The project is located within 1,000 feet of the Valley Christian Academy at 2970 Santa Maria Way in Santa Maria. A school notice pursuant to the requirements of H&SC §42301.6 is required.

10.0 PUBLIC and AGENCY NOTIFICATION PROCESS/COMMENTS ON DRAFT PERMIT

10.1 A public notice for this project will be issued, and any comments received will be included in the final permit.

10.2 Any comments that are received by the stationary source on this draft permit will be included in the final permit.

11.0 FEE DETERMINATION

Fees for this permit are assessed under the cost reimbursement provisions of Rule 210. The Project Code is 205836 (*CSC 756 Blue Ridge Dr/Trihydro - Active*).

12.0 RECOMMENDATION

It is recommended that this permit be granted with the conditions as specified in the permit.

AQ Engineer/Technician

Date

Supervisor

Date